SOUTHWESTERN PENNSYLVANIA WATER AUTHORITY 1442 JEFFERSON ROAD P.O. BOX 187 JEFFERSON, PA 15344

724-883-2301/724-627-7445/800-356-4168

INTERIOR METER SERVICE LINE SPECIFICATIONS

- 1. SERVICE LINES FROM CURB STOP TO METER MUST BE A MINIMUM OF ¾" TYPE K COPPER TUBING.
- 2. SERVICE LINES SHALL BE BURIED AT A MINIMUM DEPTH OF NO LESS THAN 36".
- 3. DISTANCE FROM CURB STOP TO WATER METER SHALL BE NO MORE THAN 300' IN LENGTH, AND MAY USE ONLY TWO (2) 3/4" COMPRESSION UNIONS, BEING A FORD C-44-33-Q, MUELLER H-15403, OR A MCDONALD 4758-Q.
- 4. ALL FITTINGS BEFORE THE WATER METER SHALL BE COMPRESSION.
- SERVICE LINES MUST BE INSPECTED BY SOUTHWESTERN PENNSYLVANIA WATER AUTHORITY PERSONNEL BEFORE BACKFILLING.
- 6. SERVICE LINE INSPECTIONS WILL BE DONE BETWEEN THE HOURS OF 8:30 A.M. TO 3:00 P.M. MONDAY THROUGH FRIDAY NO EXCEPTIONS.
- 7. A DUAL CHECK BACKFLOW PREVENTOR IS ALSO REQUIRED. WE ALSO RECOMMEND INSTALLING A SMALL EXPANSION TANK TO AVOID HOT WATER TANK POP OFF VALVES FROM OPENING.

NOTE: ANY OTHER QUESTIONS REGARDING THE INTERIOR METER INSTALLATION SHALL BE DIRECTED TO SOUTHWESTERN PENNSYLVANIA WATER AUTHORITY AT THE ABOVE PHONE NUMBERS.

TYPICAL INERIOR METER INSTALLATION

